

BRUSHLESS DC FANS


F410T

FEATURES


- Low noise 12 dB (A)
- Light weight (approx. 14 g)

STRUCTURE

- Frame and impeller
ABS/PBT alloy
- Bearing
1 sleeve bearing



PART NUMBER DESIGNATION



LIST OF PART NUMBERS

Power supply	Part number	
	Air flow	
	0.11 m ³ /min	0.15 m ³ /min
DC5 V	F410T-05LC	F410T-05MC
DC12 V	F410T-12LC	F410T-12MC

※ Verify the above part numbers when placing orders.


F410T BRUSHLESS DC FANS

STANDARD SPECIFICATIONS

Item	F410T-05LC	F410T-12LC	F410T-05MC	F410T-12MC
Rated voltage	5 V	12 V	5 V	12 V
Voltage range	4.5 ~ 5.7	10.2 ~ 13.2	4.5 ~ 5.7	10.2 ~ 13.8
Rated current	0.08 A	0.04 A	0.12 A	0.06 A
Rotating speed	4600 min ⁻¹		5800 min ⁻¹	
Air flow	0.11 m ³ /min		0.15 m ³ /min	
Static pressure	10 Pa		23 Pa	
Noise	12 dB (A)		18 dB (A)	
Net weight	Approx. 14 g			


※ Figures in the table are typical values under rated operating condition.

AIR FLOW PERFORMANCE CURVES



OUTLINE DIMENSIONS

(Unit: mm)



Specifications are subject to change without notice. Specifications in this catalog are for reference. The formal specification sheets will be submitted upon request.